

# OEM REPLACEMENT NOZZLE REAMER BLADES



The **American Weldquip** nozzle reamer blades are designed for replacement on AWQ and original OEM nozzle cleaning station equipment.

All blades are manufactured from tool steel and hardened to guarantee for long life. The dual cutting blade design provides additional cleaning action and increased durability even in high weld spatter environments.

Using genuine **American Weldquip** robotic equipment and consumables with 5/8 bore nozzles will allow you (in most cases) to ream and clear spatter accumulation past the gas holes.

All blades are manufactured by **American Weldquip** in Sharon Center Ohio so you are always guaranteed of quality you can trust.

PART NUMBER	NOZZLE BORE SIZE	OD	ID	L1	L2	THREAD TYPE	REAMER SPECIFIC
RB500	1/2" (13mm)	.490"(12.5mm)	.374"(9.5mm)	2.56"(65mm)	1.76"(44.7mm)	Female - 3/8-24	
RB-500B	1/2" (13mm)	.490"(12.5mm)	.374"(9.5mm)	2.56"(65mm)	1.76"(44.7mm)	Male - M24x1.5	Binzel
RB500-04TRG	1/2" (13mm)	.490"(12.5mm)	.374"(9.5mm)	2.56"(65mm)	1.76"(44.7mm)	Male - 3/8-24	Tregaskiss
RB560	9/16" (15mm)	.555"(14mm)	.435"(11mm)	2.56"(65mm)	1.76"(44.7mm)	Female - 3/8-24	
RB560-01	9/16" (15mm)	.535"(13.5mm)	.391"(10mm)	1.65"(42mm)	1.10"(28mm)	Male - 3/8-24	Tregaskiss
RB560-01B	9/16" (15mm)	.535"(13.5mm)	.391"(10mm)	2.11"(53.5mm)	1.10"(28mm)	Male - M24x1.5	Binzel
RB625	5/8" (16mm)	.610"(15.5mm)	.511"(13mm)	2.69"(68mm)	2.14"(54mm)	Female - 3/8-24	
RB625-01TRG	5/8" (16mm)	.610"(15.5mm)	.511"(13mm)	2.69"(68mm)	2.14"(54mm)	Male - 3/8-24	Tregaskiss
RB625-01	5/8" (16mm)	.610"(15.5mm)	.453"(11.5mm)	2.56"(65mm)	1.76"(44.7mm)	Female - 3/8-24	
RB625-02	5/8" (16mm)	.610"(15.5mm)	.511"(13mm)	2.95"(75mm)	2.10"(54mm)	Female - 3/8-24	
RB625-03	5/8" (16mm)	.590"(15mm)	.433"(11mm)	2.56"(65mm)	1.76"(44.7mm)	Female - 3/8-24	
RB625-03B	5/8" (16mm)	.590"(15mm)	.433"(11mm)	2.81"(71.4mm)	1.55"(39.4mm)	Male - M24x1.5	Binzel

